Purpose: To achieve a uniform approach when responding to and operating at Motor Vehicle Accidents [MVA's].

It shall be the goal of the NKFD to dispatch apparatus in accordance with SOG 3651 Response to Incidents.

- Incident volume or call specifics may reduce or increase the number of Companies responding to any given EMS incident. In such cases the FAO and/or shift commander will alter the initial dispatch to either adhere to minimums or increase manpower to meet specific goals.

Individual Company Assignments/Responsibilities:

Rescue Company Assignments

- Upon arrival at the scene of a Motor Vehicle Accident (MVA) it is the responsibility of the First Arriving Rescue Company to conduct the following:
    - Scene safety
    - EMS Triage
    - Identify injured person(s) most severe to least
    - Identify patients needing extrication
    - Identify which patent you will be treating
    - Establish patient contact and begin treatment

  The first due Rescue Company officer will report all findings to the IC either by face to face conference or radio communication.

Fire Company Assignments

- Upon arriving at the scene of a Motor Vehicle Accident (MVA), it is the responsibility of the first arriving Fire Company to conduct the following:

    - Establish Incident Command
    - Assume a roll as the IC
    - Assure scene safety
    - Conference with the first arriving Rescue Officer
    - Assign responsibilities to incoming apparatus
    - Ensure proper placement of apparatus
    - Request additional apparatus as needed
    - Assist with extrication and patient care

If applicable - The first due Fire Company officer will report all findings to the IC either by face to face conference or radio communication.

If applicable - The IC shall act as liaison between fire personnel and law enforcement in the placement of apparatus, lane and roadway closures, and overall incident safety and stabilization.

Once the Incident Commander is on scene and command has been established, company officers operating at MVAs shall communicate pertinent information to the IC. Direct communication with Fire Alarm shall be minimal.